

Jurisdiction and Rule Web address	Rule Number	Rule Language
ARCI Model Rule www.ua-rtip.org/industry/download_rules.html	ARCI-007-020 (2)	Facilities & Equipment- (2) The top of the rail must be at least 38 inches but not more than 42 inches above the top of the cushion. The inside rail shall have no less than a 24-inch overhang with a continuous smooth cover.
United States Flat Racing		
Arizona www.azsos.gov/public_sevices/Title_19/19-02.htm	-----	Rule Not Found
Arkansas www.dfa.arkansas.gov/offices/racingCommission/Pages/thoroughbreds.aspx	-----	Rule Not Found
California http://www.chrb.ca.gov/rules_search.htm	1472 (c) (e)	(c) The height of all outside and inside rails shall be between 38 and 42 inches from the top of the racing surface to the top of the rail. (e) All permanent inside rail posts shall be of a gooseneck-type design utilizing at least a 24-inch overhang with a continuous smooth elevated cover extending over the posts
Colorado http://www.colorado.gov/cs/Satellite/Rev-Racing/RRAC/1209030659304	-----	Rule Not Found
Delaware http://regulations.delaware.gov/AdminCode/title3/1000/1001/index.shtml#TopOfPage	-----	Rule Not Found
Florida www.myfloridalicense.com/dbpr/pmw/statutes.html	-----	Rule Not Found
Idaho http://adm.idaho.gov/adminrules/rules/idapa11/11index.htm	-----	Rule Not Found
Illinois www.state.il.us/agency/irb/	-----	Rule Not Found
Indiana www.in.gov/legislative/iac/title71.html	71 IAC 4.5-3-6(b)	(b) The top of the rail must be at least thirty-eight (38) inches but no more than forty-two (42) inches above the top of the cushion. The inside rail shall have no less than a fifteen (15) inch overhang with a continuous smooth cover.
Iowa www.state.ia.us/irgc/Content.htm#top	491- 10.2(10) e. (2)	(2) The top of the rail must be at least 38 inches but not more than 44 inches above the top of the cushion. The inside rail shall have no less than a 24-inch overhang with a continuous smooth cover.
Kansas http://krgc.ks.gov/index.php?id=25	112-11-19 2(B)3(B)	(B) be maintained at a height that measures 40" from the top of the cushion to the top of the rail (B) have a continuous smooth cover over the posts.
Kentucky www.khrc.ky.gov/rulesregs/	-----	Rule Not Found
Louisiana http://horseracing.la.gov/rules.html	-----	Rule Not Found
Maryland www.dsd.state.md.us/comar/subtitle_chapters/09_Chapters.aspx#Subtitle10	-----	Rule Not Found

Massachusetts www.mass.gov/?pageID=ocasubtopic&L=5&L0=Home&L1=Government&L2=Our+Agencies+and+Divisions&L3=State+Racing+Commission&L4=Rules+and+Regulations&sid=Eoca	-----	Rule Not Found
Michigan www.michigan.gov/mgcb/0,1607,7-120-55140_46494-168787--,00.html	-----	Rule Not Found
Minnesota www.mrc.state.mn.us/racing_rules.htm	-----	Rule Not Found
Montana www.mtrules.org/gateway/ChapterHome.asp?Chapter=32.28	-----	Rule Not Found
Nebraska www.horseracing.state.ne.us/	-----	Rule Not Found
Nevada gaming.nv.gov/stats_regs.ht	-----	Rule Not Found
New Jersey	////////////////	////////////////////////////////////
New Mexico http://nmrc.state.nm.us/dyn/rules_reg_00.html	15.2.2.8 I. (2)	(2) The top of the rail must be at least 38 inches but not more than 42 inches above the top of the cushion. The inside rail shall be no less than a 24-inch overhang with a continuous smooth cover.
New York www.racing.state.ny.us/racing/racing.home.htm	-----	Rule Not Found
North Dakota www.legis.nd.gov/information/acdata/html/Title69.5.html	-----	Rule Not Found
Ohio http://codes.ohio.gov/oac/3769	-----	Rule Not Found
Oklahoma www.ohrc.org/rulesonline.html	325:10-1-30(2)	(2) The inner and outer rails shall extend the entire length of the straightaway and around the connecting oval; it shall be at least thirty-eight inches (38") and not more than forty-two inches (42") in height, and constructed of material approved by the Commission.
Oregon http://arcweb.sos.state.or.us/rules/OARS_400/OAR_462/462_tofc.html	462-140-0130 (28)(a)(A)(B)	(a) Rails. All racing surfaces must have inner and outer rails of a design and construction approved by the commission: (A) Permanent rails must be made of a material which will take the impact of a horse without breaking away. All rail posts must be set in concrete at least 6 inches below the surface and at least 24 inches deep. The height of the rail must be 40 inches plus or minus 2 inches from the top of the cushion to the top of the rail. The top rail must be bolted or welded to the posts and should be smooth with no jagged edges. (B) For race meets or continuous race meets that are licensed to run 25 days or more per fiscal year, the inside rail shall be permanent of gooseneck design and have no less than 24-inch overhang with a continuous smooth elevated cover which entirely covers the overhang.
Pennsylvania http://www.pacode.com/secure/data/058/partIVtoc.html	-----	Rule Not Found

South Dakota http://legis.state.sd.us/rules/DisplayRule.aspx?Rule=20:04	-----	Rule Not Found
Texas www.txrc.state.tx.us/laws/racing_rules.php	RULE §309.206(b)(d)	(b) The top of the rail must be not less than 38 nor more than 42 inches above the top of the cushion (d) The rail posts must be spaced not more than 10 feet apart except for movable sections for the purpose of access. The top rail must be smooth and continuous, with no jagged edges.
Virginia www.vrc.virginia.gov/racingrules.shtml	11VAC 10-20-190 (B)3.b.	b. The rail height shall be from 38 inches to 42 inches from the top of the cushion to the top of the rail. All top rails shall be bolted to poles and shall be smooth with no jagged edges. Rail posts shall be of a gooseneck type design and shall have no less than a 24-inch overhang with a continuous smooth elevated cover over posts.
Washington www.whrc.wa.gov/?page=400	WAC 260-20-013 (6)	(6)...The top of the rail must be at least 38 inches but not more than 42 inches above the top of the cushion. The Commission, or designee must approve the design and construction of rails prior to the first race at the track
West Virginia www.wvracingcommission.com/wvrc_010.htm	-----	Rule Not Found
Wyoming http://parimutuel.state.wy.us/Rules.aspx	-----	Rule Not Found